

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name	: ALUMINIUM METAL POWDER LR
Product code	: A0017705000
Identification of the product	: Aluminium powder (stabilised) CAS No :7429-90-5 EC No :231-072-3 Annex No :013-002-00-1
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Use	: Industrial. For professional use only.
<u>1.3. Details of the supplier of the sa</u>	fety data sheet
Company identification	SUVCHEM Chaitanya Tower, 2nd Floor, Office # 206, Siddharth Nagar, S.V. Road, Goregaon (West), Mumbai - 400062, Maharashtra, India. Contact: +91 22 28725393 / 94 / 95
1.4. Emergency telephone number	Email ID: info@suvchem.com/care@suvchem.com
Phone no.	: + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification	: F; R11
	R15

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

 Physical hazards
 : Flammable liquids - Category 2 - Danger (CLP : Flam. Liq. 2) H225

 Substances and mixtures, which in contact with water, emit flammable gases - Category 1 - Danger (CLP : Water-react. 1) H260

2.2. Label elements

Labelling EC 67/548 or EC 1999/45



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

2. Hazards identification -DSD (continued) Symbol(s) Symbol(s) : F : Highly flammable R Phrase(s) : R11 : Highly flammable. R15 : Contact with water liberates highly flammable gases. : S2 : Keep out of the reach of children. S Phrase(s) S7/8 : Keep container tightly closed and dry. S43 : In case of fire, use . Contains : Aluminium powder (stabilised) Labelling Regulation EC 1272/2008 (CLP) Hazard pictograms Signal words : Danger Hazard statements : H225 : Highly flammable liquid and vapour. H260 : In contact with water releases flammable gases which may ignite spontaneously. **Precautionary statements** : P102: Keep out of reach of children. General P103: Read label before use. P101: If medical advice is needed, have product container or label at hand. Prevention : P223: Keep away from any possible contact with water, because of violent reaction and possible flash fire. P231+P232: Handle under inert gas. Protect from moisture. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment. P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking. P280: Wear protective gloves, protective clothing, eye protection, face protection. P233: Keep container tightly closed. Response : P303+P361+P353: IF ON SKIN (or hair) : Remove immediately all contaminated clothing. Rinse skin with water/shower. P335+P334: Brush off loose particles from skin. Immerse in cool water, wrap in wet bandages. P370+P378: In case of fire: Use for extinction. : P402+P404: Store in a dry place. Store in a closed container. Storage P403+P235: Store in well-ventilated place. Keep cool. Disposal considerations

: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.



MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

2. Hazards identification -DSD (continued)							
Contains	: Alu	minium powd	er (stabilise	ed)			
2.3. Other hazards							
Other hazards					be identified Julation REACI	as PBT substance or H.	vPvB
3. Composition/information	on ingredient	S					
Substance / Preparation	CA EC An	minium powd S No :7429-9 No :231-072 nex No :013-0 bstance.	00-5 -3	ed)			
Substance name Aluminium powder (stabilised) :	Contents 100 %	CAS No 7429-90-5	EC No 231-072-3	Annex No 013-002-00-1	REACH Ref.	Classification F; R11 R15	
						Flam. Liq. 2 _ H225 Water-react 1 _ H260	

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures 4.1. Description of first aid measures Inhalation : Assure fresh air breathing. Allow the victim to rest. Skin contact : Remove/Take off immediately all contaminated clothing. Brush off loose particles from skin. Immerse in cool water, wrap in wet bandages. Wash with plenty of soap and water. : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or Eye contact redness persist. : Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting. Ingestion 4.2. Most important symptoms and effects, both acute and delayed Symptoms relating to use : Not expected to present a significant hazard under anticipated conditions of normal use. Not expected to present a significant hazard under anticipated conditions of normal use. Not expected to present a significant hazard under anticipated conditions of normal use. 4.3. Indication of any immediate medical attention and special treatment needed **General information** : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).



MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

5. Fire-fighting measures

5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand. : Do not use a heavy water stream.	
Surrounding fires	: Use water spray or fog for cooling exposed containers.	
5.2. Special hazards arising from the substance or mixture		
Flammable class	: Highly flammable liquid and vapour.	
Hazardous combustion products	: Under fire conditions, hazardous fumes will be present.	
5.3. Advice for fire-fighters		
Protection against fire	: Do not enter fire area without proper protective equipment, including respiratory protection.	
Special procedures	: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.	

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders	: Equip cleanup crew with proper protection. Ventilate area.	
Technical measures	: Use special care to avoid static electric charges.	
Special precautions	: Remove ignition sources. No naked lights. No smoking.	
For non-emergency personnel	: Evacuate unnecessary personnel.	
6.2. Environmental precautions		
Environmental precautions	: Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.	
6.3. Methods and material for containment and cleaning up		
Clean up methods	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Store away from other materials. Collect spillage.	
6.4. Reference to other sections		

See section 8. Exposure controls/personal protection



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

. Handling and storage	
7.1. Precautions for safe handling	
Handling	: Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Handle empty containers with care because residual vapours are flammable. Handle under inert gas. Protect from moisture. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
Technical protective measures	: Provide good ventilation in process area to prevent formation of vapour. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, lighting,, equipment.
Special precautions	: No naked lights. No smoking.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage	: Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Ground/bond container and receiving equipment. Keep container tightly closed. Protect from moisture. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
Storage - away from	: Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.
<u>7.3. Specific end use(s)</u>	
Specific end use(s)	: None.

8. Exposure controls/personal protection

8.1. Exposure controls	
------------------------	--

Personal protection	: Avoid all unnecessary exposure.
 Respiratory protection 	: Wear approved mask.
 Hand protection 	: Wear protective gloves.
 Eye protection 	: Chemical goggles or safety glasses.
• Others	: When using, do not eat, drink or smoke.
8.2. Control parameters	
Occupational Exposure Limits	: No data available.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties



MATERIAL SAFETY DATA SHEET (MSDS) ALUMINIUM METAL POWDER LR

9. Physical and chemical properties (continued)

Physical state at 20 °C	: Solid.
Colour	: Grey powder
Odour	: Odorless
Odour threshold	: No data available.
pH value	: No data available.
Melting point [°C]	: 660.37 °C
Decomposition point [°C]	: N/A
Critical temperature [°C]	: N/A
Auto-ignition temperature [°C]	: 760 °C
Flammability (solid, gas)	: N/A
	Highly flammable liquid and vapour.
Flash point [°C]	: N/A
Boiling point [°C]	: 23270C
Initial boiling point [°C]	: N/A
Final boiling point [°C]	: N/A
Evaporation rate	: N/A
Vapour pressure [20°C]	: N/A
Vapour pressure mm/Hg	: N/A
Vapour density	: N/A
Density [g/cm3]	: 2,7
Relative density, gas (air=1)	: N/A
Relative density, liquid (water=1)	: N/A
Solubility in water [% weight]	: Insoluble in water
Solubility in water	: N/A
Log Pow octanol / water at 20°C	: No data available.
Solubility	: N/A
Viscosity at 40°C [mm2/s]	: N/A
9.2. Other information	
Explosive properties	: N/A
Explosion limits - upper [%]	: N/A
Explosion limits - lower [%]	: N/A
Oxidising properties	: No data available.

10. Stability and reactivity

10.1. Reactivity



MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

10. Stability and reactivity (continued)			
Reactivity	: Not established.		
10.2. Chemical stability			
Chemical stability	: Stable under recommended storage conditions.		
10.3. Possibility of hazardous reaction	ns		
Hazardous reactions	: In contact with water releases flammable gases which may ignite spontaneously.		
10.4. Conditions to avoid			
Conditions to avoid	: Direct sunlight. Extremely high or low temperatures. Open flame.		
10.5. Incompatible materials			
Materials to avoid	: Strong acids. Strong bases.		
10.6. Hazardous decomposition products			
Hazardous decomposition products	: Fumes. Carbon monoxide. Carbon dioxide. May release flammable gases.		

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity	
Inhalation	: Based on available data, the classification criteria are not met.
• Dermal	: Based on available data, the classification criteria are not met.
 Ingestion 	: Based on available data, the classification criteria are not met.
Corrosion	: Based on available data, the classification criteria are not met.
Irritation	: Based on available data, the classification criteria are not met.
Sensitization	: Based on available data, the classification criteria are not met.
Mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Toxic for reproduction	: Based on available data, the classification criteria are not met.
STOT-single exposure	: Based on available data, the classification criteria are not met.
STOT-repeated exposure	: Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

12. Ecological information 12.1. Toxicity **Toxicity information** : Not established. 12.2. Persistence - degradability Persistence - degradability : Biodegradable. 12.3. Bioaccumulative potential : Not established. **Bioaccumulative potential** 12.4. Mobility in soil : Not established. Mobility in soil 12.5. Results of PBT and vPvB assessment Results of PBT and vPvB assessment : The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH. 12.6. Other adverse effects : Avoid release to the environment. **Environmental precautions** 13. Disposal considerations 13.1. Waste treatment methods General : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. **Special precautions** : Handle empty containers with care because residual vapours are flammable. 14. Transport information 14.1. Land transport (ADR-RID)

Proper shipping name	: ALUMINIUM POWDER, UNCOATED
UN N°	: 1396
H.I. nr	: 423



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS) ALUMINIUM METAL POWDER LR

14. Transport information (continued) ADR - Class : 4.3 Labelling - Transport : 4.3 : Contact with water liberates highly flammable gases. ADR - Classification code : W2 ADR - Classification code : W2 ADR - Group : II ADR - Packing instructions : P410 ADR - Limited Quantity : 500 G ADR - Tunnel code : III

: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name	: ALUMINIUM POWDER, UNCOATED
UN N°	: 1396
IMO-IMDG - Class or division	: 4.3 : Contact with water liberates highly flammable gases.
IMO-IMDG - Packing group	: II
IMO- IMDG - Packing instructions	: P410
IMO-IMDG - Limited quantities	: 500 g
IMO-IMDG - Marine pollution	: No
EMS-Nr	: F-G S-O

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name	: ALUMINIUM POWDER, UNCOATED
UN N°	: 1396
IATA - Class or division	: 4.3 : Contact with water liberates highly flammable gases.
IATA - Packing group	: 11
IATA - Passenger and Cargo Aircraft	: ALLOWED
- Passenger and Cargo - Packing instruction	: 484
- Passenger and Cargo - Maximum Quantity/Packing	: 15 kg
IATA - Cargo only	: ALLOWED



MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

14. Transport information (continued	d)	
- Cargo only - Packing instruction	: 490	
- Cargo only - Maximum Quantity/	: 50 kg	
Packing IATA - Limited Quantites	: 5 kg	
ERG-Nr	: 4W	
15. Regulatory information		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
Safety, health and environmental regulations/legislation specific for the substance or mixture	: Ensure all national/local regulations are observed. e	
REACH Restrictions - Annex XVII	: The components of this product are not subject to restrictions.	
REACH Authorisation - Annex XIV	: The components of this product are not subject to authorization.	
15.2. Chemical Safety Assessment		
Chemical Safety Assessment	: It has not been carried out.	
16. Other information		
Revision	: Revision - See : *	
Abbreviations and acronyms	: PBT: persistent, bioaccumulative and toxic. vPvB: very persistent and very bioaccumulative	
Sources of key data used	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006	
List of relevant R phrases (heading 3) : R11 : Highly flammable. R15 : Contact with water liberates highly flammable gases.	
List of full text of H-statements in section 3	 H225 : Highly flammable liquid and vapour. H260 : In contact with water releases flammable gases which may ignite spontaneously. 	
Further information	: None.	



MATERIAL SAFETY DATA SHEET (MSDS)

ALUMINIUM METAL POWDER LR

In accordance with REACH Regulation (CE) Nº 1907/2006 and with CLP Regulation (CE) Nº 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its
 comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of
 the material by a properly trained person using this product.

End of document