

CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM CARBONATE AR (ANHYDROUS)

1. Product Identification

Synonyms: Pearl ash; potash; carbonic acid, dipotassium salt; salt of tartar CAS No.: 584-08-7

Product Coad: P0165205000

Molecular Weight: 138.21 Chemical Formula: K2CO3

2. Composition/Information on Ingredients

Ingredient	CAS No	Percer	nt Hazaro	dous
Potassium Carbonate	584-08-7		99 - 100%	Yes

3. Hazards Identification

Emergency Overview WARNING! CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY BE HARMFUL IF SWALLOWED. Inhalation: Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. Ingestion: Causes irritation to the gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhea. May have moderate toxic effects if consumed in large enough quantities. Ingestion of large amounts may be corrosive to mouth, throat and GI tract and produce abdominal pains, vomiting, diarrhea, and circulatory collapse. Skin Contact: Contact with dry material causes irritation. In aqueous solution it is a strong caustic and as such may have corrosive effects on the skin. Eye Contact: Causes extreme irritation, redness, pain and possibly corneal damage. Chronic Exposure: A chronic dermatitis may follow repeated contact with this substance.

4. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. Ingestion: If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately. Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard. Explosion: Not considered to be an explosion hazard. An explosion occurred after mixing sodium hydrosulfite, aluminum powder, potassium carbonate and benzaldehyde. Fire Extinguishing Media: Use any means suitable for extinguishing surrounding fire. Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: None established. Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CHS, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS) POTASSIUM CARBONATE AR (ANHYDROUS)

Personal Respirators (NIOSH Approved): For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH type N95 or better filters) may be worn. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-face positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Eye Protection: Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: Fine white granules. Odor: Odorless. Solubility: Soluble in equal parts of cold water. Specific Gravity: 2.29 pH: 11.6 Aqueous solution Boiling Point: Decomposes. Melting Point: 891C

10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage. Hazardous Decomposition Products: Contact with acids and involvement in a fire can cause carbon dioxide. Thermaldecomposition may also form potassium oxide. Hazardous Polymerization: Will not occur. Incompatibilities: Acids, chlorine trifluoride, magnesium. An explosion occurred after mixing sodium hydrosulfite, aluminum powder, potassium carbonate and benzaldehyde. Conditions to Avoid: Moisture, heat, dusting and incompatibles.

11. Toxicological Information

Oral rat LD50: 1870 mg/kg

---NTP Carcinogen----

Ingredient Known Anticipated IARC Category

Potassium Carbonate (584-08-7) No No None

12. Ecological Information

N/A

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.

15. Regulatory Information

N/A

16. Other Information

NFPA Ratings: Health: 2 Flammability: 0 Reactivity: 0 Label Hazard Warning: WARNING! CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY BE HARMFUL IF SWALLOWED. Label Precautions: Avoid breathing dust. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Label First Aid: If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention. Product Use: Laboratory Reagent.

AN ISO 9001: 2015 CERTIFIED



CHAITANYA CH5, 2nd FLOOR, OFFICE # 206, SIDDHARTH NAGAR, S.V.ROAD, GOREGAON (W), MUMBAł 400062, MH, INDIA. CONTACT: +9122 28725393 /94/ 95 | EMAILID: CARE@SUVCHEM.COM

MATERIAL SAFETY DATA SHEET (MSDS)

POTASSIUM CARBONATE AR (ANHYDROUS)

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- **SUVCHEM** shall not be responsible for any damage resulting from handling or from contact with the above product.
- SUVCHEM provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document