

# MATERIAL SAFETY DATA SHEET (MSDS)

## 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

## 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

Product code : SS0101200500 Identification of the product : 1-Butanol

CAS No :71-36-3 EC No :200-751-6 Annex No :603-004-00-6

Chemical formula : C4H10O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

SUVCHEM

Company identification Chaitanya Tower, 2nd Floor, Office # 206,

Siddharth Nagar, S.V. Road,

Goregaon (West), Mumbai - 400062,

Maharashtra, India.

Contact: +91 22 28725393 / 94 / 95

Email ID: info@suvchem.com/care@suvchem.com

1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [ Office hours ]

#### 2. Hazards identification -DSD

#### 2.1. Classification of the substance or mixture

## Classification EC 67/548 or EC 1999/45

Classification : R10

Xn; R22 R67

Xi; R37/38-41

### Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation -

Category 3 - Warning (CLP: STOT SE 3) H335

Specific Target Organ Toxicity - Single exposure - Narcotic effects - Category 3 -

Warning (CLP: STOT SE 3) H336

Serious eye damage - Category 1 - Danger (CLP : Eye Dam. 1) H318 Skin irritation - Category 2 - Warning (CLP : Skin Corr. 2) H315



# MATERIAL SAFETY DATA SHEET (MSDS)

# 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

### 2. Hazards identification -DSD (continued)

Acute toxicity, Oral - Category 4 - Warning (CLP : Acute Tox. 4) H302

Physical hazards : Flammable liquids - Category 3 - Warning (CLP : Flam. Liq. 3) H226

2.2. Label elements

### Labelling EC 67/548 or EC 1999/45

Symbol(s)

×

**Symbol(s)** : Xn : Harmful R **Phrase(s)** : R10 : Flammable.

R22: Harmful if swallowed.

R37/38: Irritating to respiratory system and skin.

R41: Risk of serious damage to eyes.

R67: Vapours may cause drowsiness and dizziness.

**S Phrase(s)** : S2 : Keep out of the reach of children.

S7/9 : Keep container tightly closed and in well-ventilated place. S13 : Keep away from food, drink and animal feedingstuffs.

S26 : In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S37/39: Wear suitable gloves and eye/face protection.

S46: If swallowed seek medical advice immediately and show this container or

label.

Contains : 1-Butanol

## Labelling Regulation EC 1272/2008 (CLP)

**Hazard pictograms** 









Signal words : Danger

Hazard statements : H226 : Flammable liquid and vapour.
H318 : Causes serious eve damage.

H302 : Harmful if swallowed. H315 : Causes skin irritation.

H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.

**Precautionary statements** 

• **General** : P102: Keep out of reach of children.

P103: Read label before use.

P101: If medical advice is needed, have product container or label at hand.



# MATERIAL SAFETY DATA SHEET (MSDS)

# 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

### 2. Hazards identification -DSD (continued)

Prevention : P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.

P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking. P280: Wear protective gloves, protective clothing, eye protection, face protection.

P271: Use only outdoors or in a well-ventilated area.

P261: Avoid breathing dust, fume, gas, mist, vapours, spray.

P233: Keep container tightly closed. P264: Wash thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

• **Response** : P302+P352: IF ON SKIN : Wash with plenty of soap and water.

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor if you feel

unwell.

P332+P313: If skin irritation occurs: Get medical advice.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position

comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated

clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse. P370+P378: In case of fire: Use for extinction.

• Storage : P403+P233: Store in well-ventilated place. Keep container tightly closed.

P403+P235: Store in well-ventilated place. Keep cool.

P405: Store locked up.

• **Disposal considerations** : P501: Dispose of this material and its container to hazardous or special waste

collection point, in accordance with local, regional, national and/or international

regulation.

Contains : 1-Butanol

2.3. Other hazards

Other hazards : The substance does not fulfil the criteria to be identified as PBT substance or vPvB

substance according to Annex XIII of Regulation REACH.

## 3. Composition/information on ingredients

Substance / Preparation : 1-Butanol

CAS No :71-36-3 EC No :200-751-6 Annex No :603-004-00-6

Substance.

Substance name Contents
1-Butanol : 100 %

**CAS No EC No** 71-36-3 200-751-6

Annex No 603-004-00-6 REACH Ref.

Classification R10 Xn; R22 R67 Xi; R37/38-41

Eye Dam 1 \_ H318 Flam. Liq. 3 \_ H226 Acute Tox. 4 (oral) \_ H302 Skin Irrit. 2 \_ H315 STOT SE 3 \_ H335 STOT SE 3 \_ H336



# MATERIAL SAFETY DATA SHEET (MSDS)

# 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

## 3. Composition/information on ingredients (continued)

Contains no other components or impurities which will influence the classification of the product.

#### 4. First aid measures

### 4.1. Description of first aid measures

Inhalation : Call a POISON CENTER or doctor if you feel unwell. Remove to fresh air and keep

at rest in a position comfortable for breathing.

**Skin contact** : Specific treatment (see on this label). Wash contaminated clothing before reuse.

Remove/Take off immediately all contaminated clothing. Get medical advice. If skin

irritation occurs: Wash with plenty of soap and water.

**Eye contact**: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Ingestion : Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting. Call a

POISON CENTER or doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms relating to use** : Swallowing a small quantity of this material will result in serious health hazard.

Causes serious eye damage.

Causes skin irritation. May cause respiratory irritation.

May cause drowsiness or dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek

medical advice (show the label where possible).

### 5. Fire-fighting measures

## 5.1. Extinguishing media

**Suitable extinguishing media** : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

**Unsuitable extinguishing media** : Do not use a heavy water stream.

**Surrounding fires** : Use water spray or fog for cooling exposed containers.

### 5.2. Special hazards arising from the substance or mixture

**Hazardous combustion products** : Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory

protection.



# MATERIAL SAFETY DATA SHEET (MSDS)

## 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

## 5. Fire-fighting measures (continued)

Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to

enter environment.

### 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection.

Ventilate area.

Avoid breathing dust, fume, gas, mist, vapours, spray.

**Technical measures** : Use special care to avoid static electric charges.

Special precautions : Remove ignition sources. No naked lights. No smoking.

For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

**Environmental precautions**: Prevent entry to sewers and public waters. Notify authorities if product enters

sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as

possible. Store away from other materials. Collect spillage.

#### 6.4. Reference to other sections

See section 8. Exposure controls/personal protection

## 7. Handling and storage

#### 7.1. Precautions for safe handling

Handling : Handle empty containers with care because residual vapours are flammable. Wash

thoroughly after handling. Wash thoroughly after handling. Wash thoroughly after handling. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

**Technical protective measures** : Provide good ventilation in process area to prevent formation of vapour.

Proper grounding procedures to avoid static electricity should be followed. Use only

non-sparking tools. Use explosion-proof electrical, ventilating, lighting, ...,

equipment.

**Special precautions** : No naked lights. No smoking. Avoid breathing dust, fume, gas, mist, vapours,

spray.



# MATERIAL SAFETY DATA SHEET (MSDS)

## 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

## 7. Handling and storage (continued)

### 7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep only in the original container in a cool, well ventilated place. Keep in fireproof

place. Keep container tightly closed. Ground/bond container and receiving

equipment.

**Storage - away from** : Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Specific end use(s) : None.

### 8. Exposure controls/personal protection

#### 8.1. Exposure controls

**Personal protection** : Avoid all unnecessary exposure.

• Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection

equipment is recommended.

• Hand protection : Wear protective gloves.

Skin protection
 Eye protection
 Others
 Wear suitable protective clothing.
 Chemical goggles or safety glasses.
 When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits : No data available.

#### 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state at 20 °C : Liquid.

Colour : Clear Colorless
Odour : Strong characteristic,
Odour threshold : No data available.
pH value : No data available.

Melting point [°C]: -90 °CDecomposition point [°C]: N/ACritical temperature [°C]: N/AAuto-ignition temperature [°C]: 3430C



## MATERIAL SAFETY DATA SHEET (MSDS)

## 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

## 9. Physical and chemical properties (continued)

Flammability (solid, gas) : Flammable.

Flammable liquid and vapour.

Flash point [°C] : 35 °C

Boiling point [°C] : 116 - 118 °C

Initial boiling point [°C] : 116 °C

Final boiling point [°C] : 118 °C

Evaporation rate : 0,46

Vapour pressure [20°C] : 5 hPa at 20 °C

Vapour pressure mm/Hg : N/A
Vapour density : 2,56
Density [g/cm3] : 0,81
Relative density, gas (air=1) : 0,81
Relative density, liquid (water=1) : N/A

Solubility in water [% weight] : In water, material soluble.

Solubility in water : N/A

Log Pow octanol / water at 20°C : No data available.

Solubility : N/A Viscosity at 40°C [mm2/s] : N/A

9.2. Other information

Explosive properties : N/A
Explosion limits - upper [%] : 11,20%
Explosion limits - lower [%] : 1,40%

Oxidising properties : No data available.

## 10. Stability and reactivity

10.1. Reactivity

Reactivity : Not established.

10.2. Chemical stability

Chemical stability : Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions : Not established.

10.4. Conditions to avoid



# MATERIAL SAFETY DATA SHEET (MSDS)

## 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

## 10. Stability and reactivity (continued)

**Conditions to avoid** : Direct sunlight. Extremely high or low temperatures. Open flame. Overheating.

Heat. Sparks.

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

10.6. Hazardous decomposition products

**Hazardous decomposition products**: Fumes. Carbon monoxide. Carbon dioxide.

May release flammable gases.

### 11. Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** 

Inhalation
 Based on available data, the classification criteria are not met.
 Dermal
 Based on available data, the classification criteria are not met.

• Ingestion : Harmful if swallowed.

**Corrosion** : Causes serious eye damage.

**Irritation** : Causes skin irritation.

May cause respiratory irritation.

Sensitization : Based on available data, the classification criteria are not met.

Mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Toxic for reproduction : Based on available data, the classification criteria are not met.

**STOT-single exposure** : May cause drowsiness or dizziness.

STOT-repeated exposure : Based on available data, the classification criteria are not met.

Aspiration hazard : Based on available data, the classification criteria are not met.

### 12. Ecological information

12.1. Toxicity

**Toxicity information** : Not established.

12.2. Persistence - degradability

Persistence - degradability : Biodegradable.

12.3. Bioaccumulative potential



# MATERIAL SAFETY DATA SHEET (MSDS)

# 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

### 12. Ecological information (continued)

Bioaccumulative potential : Not established.

12.4. Mobility in soil

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment: The substance does not fulfil the criteria to be identified as PBT substance or vPvB

substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

**Environmental precautions** : Avoid release to the environment.

### 13. Disposal considerations

#### 13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with

local/national regulations.

Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

**Special precautions** : Handle empty containers with care because residual vapours are flammable.

## 14. Transport information

### 14.1. Land transport (ADR-RID)

Proper shipping name : BUTANOLS

UN N° : 1120 H.I. nr : 30 ADR - Class : 3

**Labelling - Transport** : 3 : Flammable liquid.



ADR - Classification code : F1

F1 F1

ADR - Group : III



# MATERIAL SAFETY DATA SHEET (MSDS)

## 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

## 14. Transport information (continued)

ADR - Packing instructions : P001 R001 LP001

ADR - Limited Quantity : 5 L

**ADR** - Tunnel code



: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and

E. Other carriage: Passage forbidden through tunnels of category E.

### 14.2. Sea transport (IMDG) [English only]

Proper shipping name : BUTANOLS

**UN N°** : 1120

**IMO-IMDG - Class or division** : 3 : Flammable liquid.

IMO-IMDG - Packing group : III

IMO- IMDG - Packing instructions : P001 LP01

IMO-IMDG - Limited quantities : 5 L

IMO-IMDG - Marine pollution : No

EMS-Nr : F-E S-D

### 14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name : BUTANOLS

UN N° : 1120

IATA - Class or division : 3 : Flammable liquid.

IATA - Packing group : III

IATA - Passenger and Cargo Aircraft : ALLOWED

- Passenger and Cargo - Packing : 355

instruction

- Passenger and Cargo - Maximum : 60 L

**Quantity/Packing** 

IATA - Cargo only : ALLOWED

- Cargo only - Packing instruction : 366

- Cargo only - Maximum Quantity/ : 220 L

**Packing** 

IATA - Limited Quantites : 10 L ERG-Nr : 3L

## 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



## MATERIAL SAFETY DATA SHEET (MSDS)

## 1-BUTANOL LR (n-BUTYL ALCOHOL) (BUTAN-1-OL)

In accordance with REACH Regulation (CE) No 1907/2006 and with CLP Regulation (CE) No 1272/2008

## **DISCLAIMER:**

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

**End of document**