

MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : 1,4-DIOXAN HPLC

PΥ

Product code : SS0108401000 Identification of the product : 1.4-Dioxane

CAS No :123-91-1 EC No :204-661-8

Annex No: 603-024-00-5

Chemical formula : C4H8O2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification SUVCHEM Chaitanya Ti

Chaitanya Tower, 2nd Floor, Office # 206,

Siddharth Nagar, S.V. Road,

Goregaon (West), Mumbai - 400062,

Maharashtra, India.

Contact: +91 22 28725393 / 94 / 95

Email ID: info@suvchem.com/care@suvchem.com

1.4. Emergency telephone number

Phone no. : + 91 22 28725393 / 94 / 95 (9:00am - 6:00 pm) [Office hours]

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification : F; R11

R19

Carc. Cat. 3; R40

R66 Xi; R36/37

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards : Carcinogenicity - Category 2 - Warning (CLP : Carc. 2) H351

Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation -

Category 3 - Warning (CLP: STOT SE 3) H335

Eye irritation - Category 2A - Warning (CLP: Eye Irrit. 2) H319



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

2. Hazards identification -DSD (continued)

Physical hazards : Flammable liquids - Category 2 - Danger (CLP : Flam. Liq. 2) H225

2.2. Label elements

Labelling EC 67/548 or EC 1999/45

Symbol(s)





Symbol(s) : F : Highly flammable

Xn: Harmful

R Phrase(s) : R11 : Highly flammable.

R19: May form explosive peroxides.

R36/37 : Irritating to eyes and respiratory system. R40 : Limited evidence of a carcinogenic effect.

R66: Repeated exposure may cause skin dryness or cracking.

S Phrase(s) : S2 : Keep out of the reach of children.

S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking. S36/37: Wear suitable protective clothing and gloves.

S46: If swallowed seek medical advice immediately and show this container or

label.

Contains : 1,4-Dioxane

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms







Signal words : Danger

Hazard statements : H225 : Highly flammable liquid and vapour.

H351: Suspected of causing cancer. H319: Causes serious eye irritation. H335: May cause respiratory irritation.

Precautionary statements

• **General** : P102: Keep out of reach of children.

P103: Read label before use.

P101: If medical advice is needed, have product container or label at hand.

P201: Obtain special instructions before use.

• **Prevention** : P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.

P210: Keep away from heat, sparks, open flames or hot surfaces. - No smoking. P280: Wear protective gloves, protective clothing, eye protection, face protection.

P271: Use only outdoors or in a well-ventilated area.



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

2. Hazards identification -DSD (continued)

P261: Avoid breathing dust, fume, gas, mist, vapours, spray.

P233: Keep container tightly closed. P264: Wash thoroughly after handling.

: P308+P313: If exposed or concerned : get medical advice. Response

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position

comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated

clothing. Rinse skin with water/shower.

P337+P313: If eye irritation persists: Get medical advice/attention.

P370+P378: In case of fire: Use for extinction.

: P403+P233: Store in well-ventilated place. Keep container tightly closed. Storage

P403+P235: Store in well-ventilated place. Keep cool.

P405: Store locked up.

: P501: Dispose of this material and its container to hazardous or special waste Disposal considerations

collection point, in accordance with local, regional, national and/or international

regulation.

Contains : 1,4-Dioxane

2.3. Other hazards

Other hazards : The substance does not fulfil the criteria to be identified as PBT substance or vPvB

substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

: 1,4-Dioxane **Substance / Preparation**

CAS No:123-91-1 EC No: 204-661-8 Annex No: 603-024-00-5

Substance.

Substance name Contents CAS No EC No Annex No REACH Ref. Classification 1,4-Dioxane

100 % 123-91-1 204-661-8 603-024-00-5 F; R11 R19

Carc. Cat. 3; R40 R66 Xi; R36/37 Flam. Liq. 2 _ H225 Carc. 2 _ H351 Eye irrit 2 _ H319 STOT SE 3 _ H335 STOT RE _ EUH066 Expl. _ EUH019

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures

4.1. Description of first aid measures



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

4. First aid measures (continued)

Inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER or doctor if you feel unwell.

Skin contact : Wash with plenty of soap and water. Remove/Take off immediately all

contaminated clothing.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists : Get medical advice.

Ingestion : Obtain emergency medical attention. Do NOT induce vomiting. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use : Suspected of causing cancer.

Causes serious eye irritation. May cause respiratory irritation. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

General information : Never give anything by mouth to an unconscious person. If you feel unwell, seek

medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

Surrounding fires : Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Flammable class : Highly flammable liquid and vapour.

May form explosive peroxides.

Hazardous combustion products : Under fire conditions, hazardous fumes will be present. May form flammable/

explosive vapour-air mixture.

5.3. Advice for fire-fighters

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory

protection.

Special procedures : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to

enter environment. DO NOT fight fire when fire reaches explosives. Evacuate area.



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders : Equip cleanup crew with proper protection.

Ventilate area.

Technical measures : Use special care to avoid static electric charges.

Special precautions : Remove ignition sources. No naked lights. No smoking. Reacts vigorously with

strong oxidizers and acids.

For non-emergency personnel : Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters

sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as

possible. Store away from other materials. Collect spillage.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Handling : Handle empty containers with care because residual vapours are flammable.

Obtain special instructions before use.

Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Technical protective measures : Provide good ventilation in process area to prevent formation of vapour.

Proper grounding procedures to avoid static electricity should be followed. Use

explosion-proof electrical, ventilating, lighting, ..., equipment.

Special precautions : No naked lights. No smoking. Avoid breathing dust, fume, gas, mist, vapours,

spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep only in the original container in a cool, well ventilated place. Keep in fireproof

place. Keep container tightly closed. Ground/bond container and receiving

equipment.

Storage - away from : Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

Oxidizing agent.



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

7. Handling and storage (continued)

7.3. Specific end use(s)

Specific end use(s) : None.

8. Exposure controls/personal protection

8.1. Exposure controls

Personal protection : Avoid all unnecessary exposure.

Respiratory protection
 Hand protection
 Wear approved mask.
 Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
 Others : When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits : No data available.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state at 20 °C : Liquid.

Colour: Clear ColorlessOdour: Faint ether-like odorOdour threshold: No data available.pH value: No data available.

Melting point [°C] : 10 - 12 °C

Decomposition point [°C] : N/A

Critical temperature [°C] : N/A

Auto-ignition temperature [°C] : 180 °C Flammability (solid, gas) : Flammable.

Highly flammable liquid and vapour.

Flash point [°C] : 12 °C

Boiling point [°C] : 100 - 102 °C
Initial boiling point [°C] : 100°C
Final boiling point [°C] : 102 °C
Evaporation rate : 2,7

Vapour pressure [20°C] : 36 hPa at 20 °C



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

9. Physical and chemical properties (continued)

Vapour pressure mm/Hg : N/A
Vapour density : 3,03
Density [g/cm3] : 1,03
Relative density, gas (air=1) : 3,04
Relative density, liquid (water=1) : N/A
Solubility in water [% weight] : N/A
Solubility in water : N/A

Log Pow octanol / water at 20°C : No data available.

Solubility : 6 to 8 Viscosity at 40°C [mm2/s] : N/A

9.2. Other information

Explosive properties : N/A

May form explosive peroxides.

Explosion limits - upper [%] : 22% Explosion limits - lower [%] : 2%

Oxidising properties : No data available.

10. Stability and reactivity

10.1. Reactivity

Reactivity : Not established.

10.2. Chemical stability

Chemical stability : Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions : Not established.

10.4. Conditions to avoid

Conditions to avoid : Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.

Open flame. Direct sunlight. Overheating. Heat. Sparks. Open flame. Direct

sunlight. Overheating.

10.5. Incompatible materials

Materials to avoid : Strong acids. Strong bases.

Oxidizing agent. Oxidizing agent.

Page: 7



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

10. Stability and reactivity (continued)

10.6. Hazardous decomposition products

Hazardous decomposition products: Fumes. Carbon monoxide. Carbon dioxide.

May release flammable gases.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Inhalation
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Ingestion
 Based on available data, the classification criteria are not met.

Corrosion : Based on available data, the classification criteria are not met.

Irritation : Causes serious eye irritation.

May cause respiratory irritation. Repeated exposure may cause skin dryness or cracking.

Sensitization : Based on available data, the classification criteria are not met.

Mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Suspected of causing cancer.

Toxic for reproduction: Based on available data, the classification criteria are not met.STOT-single exposure: Based on available data, the classification criteria are not met.STOT-repeated exposure: Based on available data, the classification criteria are not met.Aspiration hazard: Based on available data, the classification criteria are not met.

12. Ecological information

12.1. Toxicity

Toxicity information : Not established.

12.2. Persistence - degradability

Persistence - degradability : Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential : Not established.

12.4. Mobility in soil



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

12. Ecological information (continued)

Mobility in soil : Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment: The substance does not fulfil the criteria to be identified as PBT substance or vPvB

substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions : Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General : Avoid release to the environment. Dispose in a safe manner in accordance with

local/national regulations.

Hazardous waste due to potential risk of explosion.

Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Special precautions : Handle empty containers with care because residual vapours are flammable.

14. Transport information

14.1. Land transport (ADR-RID)

Proper shipping name : DIOXANE UN N° : 1165 H.I. nr : 33 ADR - Class : 3

Labelling - Transport : 3 : Flammable liquid.



ADR - Classification code : F1

F1

ADR - Group : II

ADR - Packing instructions : P001 R001

ADR - Limited Quantity : 1 L



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

14. Transport information (continued)

ADR - Tunnel code



: D/E : Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name : DIOXANE UN N° : 1165

IMO-IMDG - Class or division : 3: Flammable liquid.

IMO-IMDG - Packing group **IMO-IMDG - Packing instructions** : P001 **IMO-IMDG - Limited quantities** : 1 L **IMO-IMDG - Marine pollution** : No **EMS-Nr** : F-E S-D

14.3. Air transport (ICAO-IATA) [English only]

: DIOXANE Proper shipping name UN N° : 1165

IATA - Class or division : 3 : Flammable liquid.

IATA - Packing group

IATA - Passenger and Cargo Aircraft : ALLOWED

- Passenger and Cargo - Packing

instruction

- Passenger and Cargo - Maximum : 5 L

Quantity/Packing

: ALLOWED IATA - Cargo only

- Cargo only - Packing instruction : 364 - Cargo only - Maximum Quantity/

Packing

IATA - Limited Quantites : 1 L **ERG-Nr** : 3L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental regulations/legislation specific for the

: Ensure all national/local regulations are observed.

substance or mixture



MATERIAL SAFETY DATA SHEET (MSDS)

1,4-DIOXAN HPLC

In accordance with REACH Regulation (CE) No 1907/2006 and with CLP Regulation (CE) No 1272/2008

DISCLAIMER:

- SUVCHEM Products are to be used as Lab Chemicals for R&D only. Not for drug, medicinal, household or other uses.
- SUVCHEM shall not be responsible for any damage resulting from handling or from contact with the above product.
- **SUVCHEM** provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product.

End of document